




CLIP SELECTION FOR EACH RAIL				
	F mm	K mm	H mm	Weight kg/m
A 65	175.0	65.0	75.0	43.10
A 75	200.0	75.0	85.0	56.20
A 100	200.0	100.0	95.0	74.30
A 120	220.0	120.0	105.0	100.00
A 150	220.0	150.0	150.0	150.00
S 41/10	125.0	67.0	138.0	41.38
S 41/14	125.0	67.0	138.0	40.95
S 49	125.0	67.0	149.0	49.43
UIC 54	140.0	70.0	169.0	54.43
UIC 60	150.0	72.0	172.0	60.34
GX 40	127.0	63.5	127.0	39.80
GX 42	131.8	65.1	131.8	42.16
MRS 51 (104 Lb ASCE)	127.0	63.5	127.0	51.59
MRS 52 (105 Lb ASCE)	131.8	65.1	131.8	52.09
MRS 67 (135 Lb ASCE)	131.8	76.2	146.0	66.97
MRS 73 (AS 73)	146.0	70.0	157.0	73.63
MRS 85 (171 Lb ASCE)	152.4	101.6	152.4	84.83
MRS 86 (AS 86)	165.0	102.0	102.0	85.60
MRS 87 A (PRI 85 R)	152.4	101.6	152.4	86.80
MRS 87 B (175 Lb ASCE)	152.4	102.4	152.4	86.80
MR 151 (PR 7)	220.0	150.0	150.0	151.30
JIS 37	122.2	62.7	122.2	37.20
JIS 40 N	122.0	64.0	140.0	40.90
JIS 50 N	127.0	65.0	153.0	50.40
JIS 60	145.0	65.0	174.0	60.80
CR 73	140.0	100.0	135.0	73.30
CR 100	155.0	120.0	150.0	100.20
P 43	114.0	70.0	140.0	44.65
P 50	132.0	70.0	152.0	51.67
QU 70	120.0	70.0	120.0	52.80
QU 80	130.0	80.0	130.0	63.70
QU 100	150.0	100.0	150.0	89.10
QU 120	170.0	120.0	170.0	118.10
35 BR	160.0	58.0	76.0	35.38
50 BR	165.0	58.5	76.0	50.18
56 BR	171.0	76.0	101.5	56.81
89 BR	178.0	102.0	114.0	89.81
101 BR	165.0	100.0	155.0	100.38
BS 110 A	139.7	69.9	158.8	54.52
BS 113 A	139.7	69.9	158.8	56.40
AS 41	127.0	63.5	137.0	40.72
AS 47	127.0	69.9	141.0	46.63
AS 50	127.0	69.9	154.0	50.80
AS 53	146.0	69.9	157.0	53.08
AS 60	146.0	69.9	170.0	60.99
RE 68	152.4	74.0	186.0	67.62
AS 73 (MRS 73)	146.0	70.0	157.0	73.63
AS 86 (MRS 86)	165.0	102.0	102.0	86.60

For rail sections other than those listed on this page, please contact us.

We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.

